

Mini Fix tank

LOWARA PACKAGED BREAK TANK BOOSTER SET



Mini Fix tank

The Mini single pump Fix tank booster set has been designed to be compact and provide a fluid category 5 air gap complying with the water supply (water fittings) regulations 1999 and comes as a complete package in an enclosed stainless steel cabinet suitable for wall or floor mounting.

The pump control is provided by our well proven Genyo unit which will start the pump on falling pressure and stop the pump when flow ceases.

The Genyo unit also provides low water level protection.

Applications include:

Wash down in bin stores

Dentists rinsing equipment

School laboratory water supplies

Single hosepipe supplies

Any application where category 5 protection is required


Typical duty: 0.25l/s @ 2 bar

Materials


Case:	Stainless steel
Break tank:	18lt Polyethylene
Ball valve:	Brass
Pump Body:	Ryton
Pipework & fittings:	Copper/brass/Stainless steel
Protection:	IP54
Noise Emissions:	<70dBA


Characteristic curve and performance data

50 Hz n=2900 1/min HS=0m:









Model	Po	wer	Input	Q	m³/h	0	0.1	0.3	0.6	0.9	1.2	1.5	1.8	1.9
Single-phase	kW	HP	current		l/m	0	2	5	10	15	20	25	30	32
PABLRM 15	0.37	0.50	2.5A	H metres		40	38	35	29	23.5	18	12.5	7	5

Q = Flow rate H = Total manometric head HS = Suction height Tolerance of characteristic curves in compliance with EN ISO 9906 App. A.



Xylem Water Solutions UK Limited

Millwey Rise Industrial Estate Axminster, Devon EX13 5HU - UK Tel: (+44) 01297 630230 lowaraukenquiries@xyleminc.com www.lowara.co.uk

Xylem Water Solutions Ireland Limited

50 Broomhill Close, Airton Road Tallaght - Dublin 24 Tel: (+353) 01452 4444 lowara.ireland@xyleminc.com www.lowara.ie