PUMPING STATIONS

APPLICATIONS

Individual dwelling

Commercial


PUMPING DISTANCE


14 m

WARRANTY


2 YEAR WARRANTY

SANIFOS® 110
Product Code:
SANIFOS 110 1GR SP S
Barcode:
EAN 3308815079318





Grinder
Pro X K2



SANIFOS 110 DISCHARGE KIT
Product Code: 6100
Barcode:
EAN 3308815077024



SANIFOS® 110

INSTALLER

Wastewater lifting station, single-phase version.

Less risk of clogging **due to grinder or vortex technology.**


Screw lid for easy handling.

HOMEOWNER


Automatic pump operation.

Complete drainage kit available as an option.

LIFTING STATION WITH 1 PUMP



PUMP CURVE



PACKAGING

Tank with pre-assembled hydraulic and sealing gasket
Submersible pump with float switch
Cable clamp

TECHNICAL FEATURES

TANK	**Tank volume**	110 L
	Material	Polyethylene
	Ø Inlet	2 inlets ø ext 100/110; 2 entries ø ext 40/50
	Ø Discharge pipe	DN 40 (ext. 50 mm)
	Ø Ventilation	1 x Ø ext. 75
	Maximum incoming water temperature	70°C intermittently (5 mins max)
	Incoming water connection	182 mm
PUMP	**Flow rate**	11 m³/h
	Maximum height (Q = 0 m³/h)	14 m
	Max. recommended height	11 m
	Activation system	Float
	On/off level	320/120 mm
	Voltage	220-240 / 50 Hz
	Motor power	1500 W
	Maximum current	6 A
	Thermal overload protection	Yes
	Weight of the station	23 kg

For more technical information visit, **www.saniflo.co.uk**